



RPI Equipment, LLC
26 W Main Street
Mount Ephraim, NJ 08059
(877) 757-1965 • toll free

rpiequipment.com
(856) 742-1994 • fax

MKT V2 & V5Esc EXCAVATOR MOUNTED VIBRATORY HAMMER ITEMS TO BE VERIFIED OR SUPPLIED BY CUSTOMER PRIOR TO RESERVATION

Customer Name:

Contact:

Job#/PO:

Jobsite Address:

When is the attachment needed?

Excavator Model #

Excavator Serial #

Length of Hoe Arm:

Bucket Pin Diameter:

How is Pin Retained (If retained by bolt, what diameter?)

Width of the stick at the bucket connection(max width 16.5"):

Does excavator have foot pedal? If so, is it electric or hydraulic?

What type and size fittings are on the excavator's auxiliary lines? JIS? JIC? Pipe?

How is the case drain configured? What fittings?

How does your excavator allow adjustments to flow to auxiliary lines? Computer?

What type and size piles will be driven? Flange size?

PLEASE NOTE: BUCKET AND/OR QUICK DISCONNECTS MUST BE REMOVED PRIOR TO SET UP. MACHINE MUST BE CAPABLE OF SUPPLYING THE FOLLOWING HYDRAULIC REQUIREMENTS FROM BUCKET CYLINDER OR BI-DIRECTIONAL AUXILIARY CIRCUIT:

V2Esc: 45 GPM @ 2,500 PSI

V5Esc: 85 GPM @ 3,000 PSI