



RPI Equipment, LLC
26 W Main Street
Mount Ephraim, NJ 08059
(877) 757-1965 • toll free

rpiequipment.com
(856) 742-1994 • fax

**MKT V2 & V5Esc EXCAVATOR MOUNTED VIBRATORY HAMMER
ITEMS TO BE VERIFIED OR SUPPLIED BY CUSTOMER PRIOR TO RESERVATION**

PLEASE NOTE: Maximum stick width to fit our attachment is 16.5" inches – can pin directly to the stick or to a quick coupler

Customer Name:

Contact:

Job#/PO:

Jobsite Address:

When is the attachment needed?

Excavator Model #

Excavator Serial #

Length of Hoe Arm:

Bucket Pin Diameter:

Link Pin Diameter:

How is Pin Retained (If retained by bolt, what diameter?)

Width of the stick at the bucket connection (max width 16.5"- please note if using QD):

Does excavator have foot petal? If so, is it electric or hydraulic?

What type and size fittings are on the excavator's auxiliary lines? JIS? JIC? Pipe, Flat Face O Ring?

*How is the case drain configured? What fittings? **Please note min size is 3/4"***

How does your excavator allow adjustments to flow to auxiliary lines? Computer?

How much auxiliary flow does your excavator put out (dedicated to attachment)?

What type and size piles will be driven? Flange size?

**MACHINE MUST BE CAPABLE OF SUPPLYING THE FOLLOWING HYDRAULIC REQUIREMENTS FROM ONE DIRECTION
AUXILIARY CIRCUIT:**

V2Esc: 45 GPM @ 2,500 PSI

V5Esc: 85 GPM @ 3,000 PSI