








Anvil™
(Owen™ Type)

DX

EXTRA HEAVY DUTY CLAMSHELL BUCKETS



SPECIFICATIONS

SIZE NUMBER		36	136	236	140	148	248	54	160	260	360	168	268	368
RATING	Cu. Yds.	3/4	1	1-1/4	1-1/4	1-1/2	2	2	2-1/2	3	3-1/2	4	4-1/2	5
	Cu. Ft.	20-1/4	27	33-3/4	33-3/4	40-1/2	54	54	67-1/2	81	94-1/2	108	121-1/2	135
CAPACITY – CU. FT.	Water Level	16-7/8	25	31-3/4	30-7/8	39-1/4	48-3/4	47-3/4	60-1/2	74-1/2	78-3/4	83	94	105
	Line of Plate	21-1/4	29	35-1/2	38-1/8	49-1/8	62	62-1/4	77-1/4	97-3/4	102	108	124	139
	Heaped Load	28-3/8	36-3/4	44-3/4	45-7/8	65-1/4	79-5/8	80	100-1/2	124-1/2	130	136	156	175
DECK AREA – SQ. FT.		20.8	23.0	24.9	26.2	37.2	40.7	43.8	50.3	55.5	60.6	71.9	73.4	78.6
DIMENSIONS	Width Outside	3'3"	3'3"	3'3"	3'7"	4'3"	4'3"	4'10"	5'5"	5'5"	5'5"	6'2"	6'2"	6'2"
	Length Open	6'5"	7'1"	7'8"	7'11"	8'9"	9'7"	9'5"	10'3"	11'0"	11'3"	11'11"	12'6"	13'1"
	Length Closed	5'11"	6'7"	7'2"	7'5"	7'7"	8'4"	7'10"	8'8"	9'5"	9'7"	10'1"	10'5"	11'0"
	Height Open	8'6"	8'11"	9'2"	9'9"	10'10"	11'6"	11'3"	10'8"	12'8"	13'3"	14'3"	14'4"	15'1"
	Height Closed	6'7"	7'3"	7'4"	7'10"	9'0"	9'5"	9'4"	10'1"	10'6"	10'11"	11'9"	12'2"	12'5"
SHEAVES	No.	5	5	5	5	5	5	5	5	5	5	5	5	5
	O.D.	14"	14"	14"	16"	18"	18"	18"	20"	20"	23"	25"	25"	25"
SIZE OF CABLE		7/8"	7/8"	7/8"	7/8"	1"	1"	1"	1"	1"	1-1/8"	1-1/8"	1-1/4"	1-1/4"
CABLE TO REEVE		44'	46'	49'	49'	56'	60'	59'	58'	70'	74'	80'	80'	84'
CABLE TO CLOSE		25'	28'	30'	30'	31'	34'	34'	30'	41'	42'	45'	45'	48'
WEIGHT	Bucket Only	4,630	4,970	5,080	5,500	9,470	9,870	10,530	13,170	13,800	14,755	22,100	23,360	23,605
	Standard Jacket	390	390	390	470	1,030	1,030	1,150	1,370	1,370	1,370	2,225	2,225	2,225
	Heavy Jacket	685	685	685	790	*	*	*	*	*	*	*	*	*
	Bottom Teeth	385	385	385	385	630	630	630	945	945	945	1,450	1,450	1,450
	Corner Teeth	50	50	50	50									
With Std. Jacket & Bottom Teeth		5,405	5,475	5,855	6,355	11,130	11,530	12,310	15,485	16,115	17,070	25,775	26,035	27,280
BOTTOM TEETH – QTY.		7	7	7	7	7	7	7	9	9	9	7	7	7

*Heavy jackets of varying weights available for models indicated.

The above data is for square nose buckets. Information for round nose buckets is approximately the same.

Because of normal variances in the material used, the weight of an actual bucket may vary slightly from that listed in the data table.

Sheaves, sockets and wedges provided for rope size as shown above unless otherwise specified.

Type DX Buckets are not drilled for side or corner teeth unless specified.

ANVIL™ OWEN™ YAUN-WILLIAMS™
attachments

Engineered and marketed by



INTERGY, INC.



RPI Equipment, LLC
26 W Main Street
Mount Ephraim, NJ 08059

rpiequipment.com
(856) 456-0081 • office
(856) 742-1994 • fax